

MODEL: GT-BS04

Oder Code	GT-BS04 (Old Model: GT-3520)
LED	3W/Pcs Cree
Row	Single Row
Operating Voltage	10-30V DC
Operating Temp	-40~+60°Celcius
Beam Pattern	Spot
Color Temperature	6000K
Lifetime	30000+h
Lens Material	Polycarbonate
Housing Material	Aluminum
Coating Powder	Sand Black
Mounting System	304 Stainless Steel Side Mount
Pressure Equalization Vent	Yes
Waterproof Rate	IP67
EMC Protection	ECE R10
Beam Type Protection	ECE R112



MODEL	Size	Watt	AMP Draw	Leds	Theoretical Lumen	Cable Length
GT-BS04-6L	7.30"	18W	1.00A@12V, 0.50A@24V	6PCS*3W	1560Lm	400mm
GT-BS04-12L	13.40"	36W	2.00A@12V, 1.00A@24V	12PCS*3W	3120Lm	400mm
GT-BS04-18L	19.70"	54W	3.00A@12V, 1.50A@24V	18PCS*3W	4680Lm	600mm
GT-BS04-24L	25.80"	72W	4.00A@12V, 2.00A@24V	24PCS*3W	16240Lm	800mm
GT-BS04-36L	32.00"	108W	6.00A@12V, 3.00A@24V	36PCS*3W	9360Lm	800mm
GT-BS04-42L	44.30"	126W	7.00A@12V, 3.50A@24V	42PCS*3W	10920Lm	800mm
GT-BS04-48L	50.60"	144W	8.00A@12V, 4.00A@24V	48PCS*3W	12480Lm	800mm

